



Bearing No. GEH 35 TXG3E-2LS

D	62 mm
d	35 mm
B	35 mm
C	22 mm
?	15 °
?	15 °
Size (mm)	62x35x35
Lubricant	Maintenance free – dry lubrication
Width (mm)	35
dk	53 mm
dk	53 mm
Bearing number	GEH 35 TXG3E-2LS
Sealing solution	Triple-lip seals
Da max.	57.5 mm
Da min.	54.5 mm
da max.	39.7 mm
da min.	39 mm
r2 min.	1 mm
r1 min.	0.6 mm
ra max.	0.6 mm
rb max.	1 mm
Mass plain bearing	0.39 kg
Bore Diameter (mm)	62
Outer Diameter (mm)	35
da - min.	39 mm
rb - max.	1 mm
ra - max.	0.6 mm
Da - max.	57.5 mm
Da - min.	54.5 mm

d_a - max.	39.7 mm
r_2 - min.	1 mm
r_1 - min.	0.6 mm
Basic dynamic load rating C	280 kN
Basic dynamic load rating - C	280 kN
Specific dynamic load factor K	300 N/mm ²
Specific factor dynamic load - K	300 N/mm ²
Basic static load rating C_0	465 kN
Basic static load rating - C_0	465 kN
Specific static load factor K_0	500 N/mm ²
Specific factor static load - K_0	500 N/mm ²
Design (sliding contact surface combination)	Steel/PTFE fabric