



Bearing No. GEH 60 TXG3A-2LS

D	105 mm
d	60 mm
B	63 mm
C	40 mm
?	17 °
?	17 °
Size (mm)	105x60x63
Lubricant	Maintenance free – dry lubrication
Width (mm)	63
d _k	92 mm
d _k	92 mm
Bearing number	GEH 60 TXG3A-2LS
Sealing solution	Triple-lip seals
D _a max.	99 mm
D _a min.	92 mm
d _a max.	67 mm
d _a min.	67 mm
r ₂ min.	1 mm
r ₁ min.	1 mm
r _a max.	1 mm
r _b max.	1 mm
Mass plain bearing	2.01 kg
Bore Diameter (mm)	105
Outer Diameter (mm)	60
d _a - min.	67 mm
r _b - max.	1 mm
r _a - max.	1 mm
D _a - max.	99 mm
D _a - min.	92 mm

d _a - max.	67 mm
r ₂ - min.	1 mm
r ₁ - min.	1 mm
Basic dynamic load rating C	880 kN
Basic dynamic load rating - C	880 kN
Specific dynamic load factor K	300 N/mm ²
Specific factor dynamic load - K	300 N/mm ²
Basic static load rating C ₀	1460 kN
Basic static load rating - C ₀	1460 kN
Specific static load factor K ₀	500 N/mm ²
Specific factor static load - K ₀	500 N/mm ²
Design (sliding contact surface combination)	Steel/PTFE fabric