



## Bearing No. 30317DJR

D	180 mm
d	85 mm
T	44,5 mm
B	41 mm
C	28 mm
a	56,3 mm
e	0.83
Cr	328
Cu	42.6
Y0	0.40
Y1	0.73
C0r	317
Bore	3.346 Inch   85 Millimeter
Noun	Bearing
a(mm)	56.3
Da min	143 mm
da max	103 mm
Weight	4,81 Kg
r min.	4 mm
r(min)	4
UNSPSC	31171516
Db(min)	169
db(max)	103
Da(max)	166
Da(min)	143
r1(min)	3
Sa(min)	6
Sb(min)	16.5
ra(max)	3

rb(max)	2.5
da(min)	103
ra max.	3 mm
Db min.	169 mm
Da max.	166 mm
da min.	103 mm
r2 min.	3 mm
rb max.	2,5 mm
Oil lub.	2600
Category	Tapered Roller Bearings Assembly
Size (mm)	85x180x44.5
Component	Assembly
Inventory	0.0
Width (mm)	44,5
Grease lub.	1900
Bearing No.	30317DJR
Basic Number	30317
Weight / LBS	10.604
Inch - Metric	Metric
Product Group	B04334
Other Features	High Load Capacity   Steep Contact Angle
Keyword String	Tapered
Assembly Width	1.752 Inch   44.5 Millimeter
Bearing number	30317DJR
Precision Class	Standard
(Refer.)Mass(kg)	4.81
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Long Description	Assembly; Standard Precision; 85MM Bore; 180MM Outside Diameter; 44.5MM

	Assembly Width; Single Row of Rollers
Outside Diameter	7.087 Inch   180 Millimeter
Weight / Kilogram	4.81
Manufacturer Name	KOYO
Bore Diameter (mm)	85
Outer Diameter (mm)	180
Minimum Buy Quantity	N/A
Number of Tapered Rows	Single Row
Harmonized Tariff Code	8482.20.00.00
Calculation factor (e)	0,83
Flange Outside Diameter	0 Inch   0 Millimeter
(Oil) Lubrication Speed	2600 r/min
Calculation factor (Y0)	0,4
Manufacturer Item Number	30317DJR
(Grease) Lubrication Speed	1900 r/min
Basic static load rating (C0)	317 kN
Basic dynamic load rating (C)	263 kN