



Bearing No. 30317J2

| | |
|------------------------|-------------|
| D | 180 mm |
| d | 85 mm |
| T | 44,5 mm |
| B | 41 mm |
| C | 34 mm |
| a | 35 mm |
| d1 | 126 mm |
| Weight | 4,85 Kg |
| db min | 99 mm |
| Da min | 156 mm |
| da max | 107 mm |
| Ca min. | 6 mm |
| Cb min. | 10,5 mm |
| Db min. | 167 mm |
| Da max. | 166 mm |
| r1 min. | 4 mm |
| r4 min. | 3 mm |
| r3 min. | 3 mm |
| r2 min. | 4 mm |
| rb max. | 3 mm |
| ra max. | 4 mm |
| Size (mm) | 85x180x44.5 |
| Width (mm) | 44,5 |
| Limiting speed | 4000 r/min |
| Bearing number | 30317J2 |
| Reference speed | 2800 r/min |
| Bore Diameter (mm) | 85 |
| Outer Diameter (mm) | 180 |
| Calculation factor (e) | 0,35 |
| Calculation factor (Y) | 1,7 |
| | |

| | |
|-------------------------------|--------|
| Fatigue load limit (Pu) | 40,5 |
| Basic dynamic load rating (C) | 303 kN |
| Basic static load rating (C0) | 365 kN |