



Bearing No. NUP212EM

B	22 mm
r	1.5
d	60 mm
D	110 mm
S	1,2 mm
C	22 mm
da	68
rb	1.5
ra	1.5
C0	107
B_	22
Fw	72 mm
Z_	16
r1	1.5
D_	110
DA_	14
DE_	100
DI_	72
SBRG	2
KBRG	4165
SDM_	86
yobi	NUP212EM
mass	0.966
C_conv	97500
r min.	1,5 mm
dc min	75
LangID	1
ALPHA_	0
db max	70
dd min	80

db min	68 mm
rb max.	1,5 mm
D_a max	102
da min.	68 mm
r1 min.	1,5 mm
Da max.	102 mm
hidYobi	NUP212EM
TSR rpm	6300
db max.	70 mm
GRS rpm	5300
Oil rpm	6300
ra max.	1,5 mm
hidTable	ecat_NSCLDR
Size (mm)	60x110x22
Macha rpm	7500
Width (mm)	22
Prod_Type3	CRB_SR_NUP
Bearing number	NUP212EM
Bore Diameter (mm)	60
Outer Diameter (mm)	110
(Grease) Lubrication Speed	6000 r/min
Basic static load rating (C0)	107 kN
Basic dynamic load rating (C)	97,5 kN