



Bearing No. 23048RHA

| | |
|------------------------|------------|
| D | 360 mm |
| d | 240 mm |
| B | 92 mm |
| C | 92 mm |
| e | 0.24 |
| Cu | 166 |
| Y1 | 2.83 |
| Y0 | 2.77 |
| Y2 | 4.21 |
| Cr | 1470 |
| C0r | 2180 |
| r(min) | 3 |
| Weight | 31,9 Kg |
| r min. | 3 mm |
| ra max. | 2,5 mm |
| Da max. | 346 mm |
| ra(max) | 2.5 |
| Da(max) | 346 |
| da(min) | 254 |
| da min. | 254 mm |
| Oil lub. | 1100 |
| Size (mm) | 240x360x92 |
| Width (mm) | 92 |
| Grease lub. | 860 |
| Bearing No. | 23048RHA |
| Bearing number | 23048RHA |
| (Refer.)Mass(kg) | 31.9 |
| Bore Diameter (mm) | 240 |
| Outer Diameter (mm) | 360 |
| Calculation factor (e) | 0,24 |
| | |

| | |
|-------------------------------|------------|
| Calculation factor (Y1) | 2,83 |
| Calculation factor (Y0) | 2,77 |
| (Oil) Lubrication Speed | 1100 r/min |
| (Grease) Lubrication Speed | 860 r/min |
| Basic static load rating (C0) | 2180 kN |
| Basic dynamic load rating (C) | 1170 kN |