



Bearing No. HM807040/HM807010

e	0.49
d	44,45 mm
D	104,775 mm
T	36,512 mm
B	36,512 mm
C	28,575 mm
a	29,7 mm
Da	89 mm
B_	36.512
Db	100 mm
da	66 mm
Y0	0.68
db	59 mm
C0	192
D_	104.775
Z_	18
C_	28.575
Y1	1.2
DE_	89.763
SLR	27
D_a	89
DI_	68.111
DA1	12.523
DA2	10.412
CUP	0.502
DA_	11.473
D_b	100
RAr	159.506
SDM_	79.264
KBRG	3161

yobi	HM807040/HM807010
CONE	1.14
ALP21	36
ALP22	0
ALP23	0
BETA_	2
BET21	4
BET23	0
BET22	30
r min.	3,5 mm
LangID	1
Weight	1,642 Kg
ALPHA_	18
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	4800
outer r	3.3
hidYobi	HM807040/HM807010
GRS rpm	3400
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	44.45x104.775x36.512
SHOG_yobi	HM807040R/HM807010 R
Prod_Type3	TRBSR_ID_A
Width (mm)	36,512
Bearing number	HM807040/HM807010
Bore Diameter (mm)	44,45
Outer Diameter (mm)	104,775
Calculation factor (e)	0,49

(Oil) Lubrication Speed	4800 r/min
Calculation factor (Y0)	0,68
(Grease) Lubrication Speed	3400 r/min
Basic static load rating (C0)	192 kN
Basic dynamic load rating (C)	139 kN