



Bearing No. 23072RHA

| | |
|------------------------|-------------|
| D | 540 mm |
| d | 360 mm |
| B | 134 mm |
| C | 134 mm |
| e | 0.23 |
| Cu | 334 |
| Y1 | 2.92 |
| Y0 | 2.85 |
| Y2 | 4.34 |
| Cr | 3040 |
| C0r | 4770 |
| r(min) | 5 |
| Weight | 105 Kg |
| r min. | 5 mm |
| ra max. | 4 mm |
| Da max. | 518 mm |
| ra(max) | 4 |
| Da(max) | 518 |
| da(min) | 382 |
| da min. | 382 mm |
| Oil lub. | 660 |
| Size (mm) | 360x540x134 |
| Width (mm) | 134 |
| Grease lub. | 500 |
| Bearing No. | 23072RHA |
| Bearing number | 23072RHA |
| (Refer.)Mass(kg) | 105 |
| Bore Diameter (mm) | 360 |
| Outer Diameter (mm) | 540 |
| Calculation factor (e) | 0,23 |

| | |
|-------------------------------|-----------|
| Calculation factor (Y1) | 2,92 |
| Calculation factor (Y0) | 2,85 |
| (Oil) Lubrication Speed | 660 r/min |
| (Grease) Lubrication Speed | 500 r/min |
| Basic static load rating (C0) | 4770 kN |
| Basic dynamic load rating (C) | 2420 kN |